




RCCN 日成MB型尼龙铆钉 Mounting Button




材质:UL合格之NYLON66(黑色)防火等级94V-2,不易老化.
用途:PC板及机板之固定,取代螺丝,不需工具即可完成装配.
特点:容易固定.
用法:先将机板及被固定板钻孔,再将本产品塞入,即可使两板相线合.
板厚:以H长度小5mm为准.
开孔:建议表格孔径负公差0.2-1mm开孔.

Material : NYLON66 UL approved,
Fireproof :94V-2,
Good quality,easy to install

单位/Unit:mm

型号 Item No.	头部 Head W	孔径 Hole dia. W1	长度 Length H	包装 Packing pcs
MB5-1145	9.2	5.5	7.5	100pcs
MB6-219	16	6.0	10.0	100pcs
MB6-143	14	6.0	15.0	100pcs
MB6-621	12	6.0	9.0	100pcs
MB6-587	10	6.0	10.0	100pcs
MB6-663	11	6.0	8.0	100pcs
MB6-86	14.1	6.0	10.5	100pcs
MB7-79	18.1	7.0	15.0	100pcs
MB7-99	18.3	7.0	12.2	100pcs
MB7-492	20	7.0	16.0	100pcs
MB7-665	25	7.0	10.0	100pcs
MB7-229	8*18	7.0	15.0	100pcs
MB8-94	15.3	8.0	15.0	100pcs
MB8-93	18.3	8.0	15.5	100pcs
MB8-540	18	8.0	15.0	100pcs
MB8-77	18.5	8.0	17.3	100pcs
MB10-87	20.1	10.0	20.4	100pcs
MB10-217	26	10.0	8.0	100pcs

RCCN 日成SR型捶式尼龙铆钉 Mounting Button



材质:UL合格之NYLON66.
防火等级:94V-2,不易老化.
用途:PC板及机板之固定,取代螺丝,不需工具即可完成装配.
特点:容易固定.
用法:先将机板及被固定板钻孔,再将本产品塞入,即可使两板相线合.
板厚:以H长度小3mm为准.
开孔:建议比表格孔径负公差0.5-1mm开孔.

说明:SR6-216与SR-0614B为同款,默认型号统一SR-0614B

Material : NYLON66 UL approved.
fireproof :94V-2
Good quality,easy to install

单位/Unit:mm

型号 Item No.	头部 Head W	孔径 Hole dia. W1	长度 Length H	包装 Packing pcs
SR4-178	7	4.5	9.5	100pcs
SR6-511	11	6.0	10.0	100pcs
SR6-216	16	6.0	14.0	100pcs
SR5-236	10	5.0	6.0	100pcs
SR5-429	11	5.0	7.0	100pcs
SR8-1150	16	8.0	12.0	100pcs
SR8-883	13	8.0	14.0	100pcs
SR8-947	12.5	8.4	12.0	100pcs
SR9-678	16	9.0	14.0	100pcs

